

RKT 9 RDO X01 EAGLE AXS



		(A) TT LENGTH	(B) SEAT TUBE LENGTH	(C) CHAINSTAY LENGTH ACTUAL	(D) HORIZONTAL CHAINSTAY	(E) FRONT CENTER	(F) WHEELBASE	(G) BB DROP	(H) HEADTUBE LENGTH	(I) HEADTUBE ANGLE	(J) SEATTUBE ANGLE	(K) STANDOVER HEIGHT	(L) REACH	(M) STACK									
METRIC (MM)	FORK TRAVEL (MM)*	100	120	—	—	100	120	100	120	100	120	100	120	100	120	100	120	100	120				
	XS	555	559	381	440	439	636	642	1074	1080	35.0	28.0	95	70.5	69.5	74.5	73.5	696	703	393	383	584	590
	SM	570	574	406	440	439	646	652	1084	1090	35.0	28.0	100	71.0	70.0	74.5	73.5	702	710	406	396	591	597
	MD	590	594	457	440	439	667	672	1103	1111	35.0	28.0	110	71.0	70.0	74.5	73.5	728	739	424	413	600	607
	LG	610	614	509	440	439	687	693	1125	1132	35.0	28.0	120	71.0	70.0	74.5	73.5	763	773	441	431	609	617
	XL	630	634	559	440	439	708	713	1146	1152	32.0	28.0	130	71.0	70.0	74.5	73.5	802	812	458	448	619	626

		(A) TT LENGTH	(B) SEAT TUBE LENGTH	(C) CHAINSTAY LENGTH ACTUAL	(D) HORIZONTAL CHAINSTAY	(E) FRONT CENTER	(F) WHEELBASE	(G) BB DROP	(H) HEADTUBE LENGTH	(I) HEADTUBE ANGLE	(J) SEATTUBE ANGLE	(K) STANDOVER HEIGHT	(L) REACH	(M) STACK									
IMPERIAL (INCH)	FORK TRAVEL (MM)*	100	120	—	—	100	120	100	120	100	120	100	120	100	120	100	120	100	120				
	XS	21.9	22.0	15.0	17.3	17.3	25.0	25.3	42.3	42.5	1.38	1.1	3.7	70.5	69.5	74.5	73.5	27.4	27.7	15.5	15.1	23.0	23.2
	SM	22.4	22.6	16.0	17.3	17.3	25.4	25.7	42.7	42.9	1.38	1.1	3.9	71.0	70.0	74.5	73.5	27.6	28.0	16.0	15.6	23.2	23.5
	MD	23.2	23.4	18.0	17.3	17.3	26.2	26.5	43.4	43.7	1.38	1.1	4.3	71.0	70.0	74.5	73.5	28.7	29.1	16.7	16.3	23.6	23.9
	LG	24.0	24.2	20.0	17.3	17.3	27.1	27.3	44.3	44.6	1.38	1.1	4.7	71.0	70.0	74.5	73.5	30.0	30.4	17.4	17.0	24.0	24.3
	XL	24.8	25.0	22.0	17.3	17.3	27.9	28.1	45.1	45.4	1.38	1.1	5.1	71.0	70.0	74.5	73.5	31.6	32.0	18.0	17.6	24.4	24.6

GEOMETRY KEY

HEIGHT RECOMMENDATIONS

X-SM	SM	MED	LG	X-LG
5'-0"–5'5"	5'3"–5'9"	5'8"–6'0"	5'11"–6'3"	6'3"–6'7"
1.53–1.65M	1.6–1.75M	1.73–1.83M	1.8–1.91M	1.91–2.01M

FOR RIDERS WHO FALL BETWEEN SIZES WE RECOMMEND SIZING DOWN FOR A MORE MANEUVERABLE RIDE OR SIZING UP FOR MORE STABILITY.

THE BEST WAY TO DETERMINE WHICH SIZE IS FOR YOU IS TO TEST RIDE A NINER AT ONE OF OUR DEALERS OR DEMO EVENTS.