



XTX 200	
Connections	Yoke and DIN available
Type of first stage	Over-balanced diaphragm design, environmentally sealed
Body Type	One piece forged body
Number of HP ports	2 (7/16" UNF)
Number of MP ports	4 with 5th port option (3/8" UNF)
Environmental Dry Kit	Standard
First stage exterior	Chrome over marine brass
Orientation	Convertible LH or RH
Coldwater Use	Yes
Type of second stage	pneumatically balanced
Opening Effort Control Knob	Yes
Integrated Venturi Lever	Yes
Mouthpiece	Comfo-bite™
Exhaust tee	Diver Changeable - comes with 2 sets
Heat Exchanger for freezing resistance	YES
Hose type	Braided Flexi-hose
Overall work of breathing (WOB) scores	Avg. 0.70 joules/liter
Nitrox compatible	Yes to 40% O2 when new, out of the box / Can be cleaned to 100%
Weight	Yoke 1272g / DIN 1142g
OCTOPUS XTX 40	
Orientation	Convertible LH or RH
Coldwater Use	Yes
Type of second stage	Pneumatically balanced
Integrated Venturi Lever	Yes
Mouthpiece	Comfo-bite™
Heat Exchanger for freezing resistance	Yes
Hose type	Braided Flexi-hose
Nitrox compatible	Yes to 40% O2 when new, out of the box / Can be O2 cleaned to 100%