

Number of models	4- Legend LX yoke, Legend LX DIN, Legend LX Supreme yoke, Legend LX Supreme DIN
Type of first stage	Over-balanced diaphragm design, environmentally sealed
First stage weight yoke / din (grams)	882 / 668
First stage length (mm)	74.7
Auto-Closure Device (ACD)	YES
First stage MP chamber	Enlarged, symmetrical, all ports provide equal access
Number of HP ports	2
Number of MP ports	4
Environmental Dry Kit	Standard
First stage exterior	Chrome over marine brass
First stage handwheel	Triangular shape with oversized soft grip ribs, auto-drain
First stage dust cap	Redesigned so it will not inadvertently open the auto-closure device (ACD)
Type of second stage	Pneumatically balanced
Second stage weight - (grams)	200
Second stage diameter (cm)	6.57
Controls	One control, the MBS, adjusts both the venturi and the opening effort
Breathing resistance	User adjustable
Mouthpieces	2 - Comfobite installed, standard with bite wings in box
Front cover	Co-molded w/ limited range to control purge flow rate
Exhaust tee	Re-designed for better bubble dispersion and easier exhalation
Lip shield	YES
Heat Exchanger for freezing resistance	YES
Hose type	29" braided AquaFlex hose
Hydrodynamic openings	Lateral
Overall work of breathing (WOB) scores	Avg. 0.65 joules/liter
Nitrox compatible	Yes to 40% O2 when new, out of the box