

AXIS T8133 30 W Midspan

Widely used for PoE-based devices

Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. A midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. AXIS T8133 30 W Midspan is a 1-port midspan, delivers 30 W and is IEEE 802.3at compliant, which ensures compatibility with most of Axis network products with built-in PoE.

- > IEEE 802.3at
- > 100 to 240 V AC
- > Plug-and-play



AXIS T8133 30 W Midspan

Midspans		General	
Function	Data and power are fed to a network video product through an Ethernet cable Us together with a PoE splitter for a network video product without built-in PoE support	Sustainability	PVC free
Data rate	10/100/1000 Mbps	Display and indicators	LEDs are located on the front panel Port LED: power indicator and data connectivity
Installation and management	Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display Should be used with a non-PoE network switch. If a PoE switch is used, turn off the PoE on the port in use	Mounting	Wall, shelf or DIN rail ^a
Data & power		Operating conditions	At 22.5 W: -20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–90% RH (non-condensing) -20 °C to 60 °C -20 °C to 40 °C (-4 °F to 104 °F) -20 °C to 50 °C
Power	Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4	Approvals	RoHS, REACH, WEEE, CE, EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IS 13252, GS, CB, CCC
Input	AC input voltage: 100 to 240 V AC AC frequency: 50–60 Hz	Dimensions	35 x 52 x 141 mm (1.3 x 2.0 x 5.5 in)
Output	55 V DC (max 30 W)	Weight	200 g (0.4 lb)
Power consumption	No remote device connected: 2 W 30 W remote device connected: 36 W	Included accessories	Installation guide
Connectors	Shielded RJ45, EIA 568A and 568B Power connector C13	Optional accessories	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13–Open 0.5 m For more accessories, see axis.com
Wiring	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over spare pairs 4/5 (+) and 7/8 (-)	Warranty	3-year warranty, see axis.com/warranty

a. Sold as optional accessory

Environmental responsibility:

axis.com/environmental-responsibility