

AXIS T91B51 Ceiling Mount Ceiling mount for PTZ and fixed domes

The outdoor and indoor, AXIS T91B51 Ceiling Mount is ideal where a PTZ dome or a fixed dome camera needs to be installed in low ceilings or in roof overhangs. If a longer length is needed, two optional extension pipes are available, 30 cm (12 in) and 100 cm (39 in). The ceiling mount is designed to swing and not break if hit by forklifts or tall vehicles. It can also be installed in sloped ceilings thanks to the ball joint, which ensures that the camera is still hanging straight.

- > For outdoors and indoors
- > Robust and safe installation
- > Support for Axis PTZ domes and fixed domes with 1.5" NPS thread
- > Flexible length, up to 5 m (197 in) with extension pipes
- > Swivel action with a $\pm 45^{\circ}$ pivot angle





AXIS T91B51 Ceiling Mount

General		Cable routing	Side: Cable conduit hole 3/4"
Supported products	AXIS P55/P56/Q60/Q61 Series (requires AXIS T94A01D Pendant Kit) AXIS M50 Series (requires AXIS T91A05 Camera Holder 1.5" NPS) AXIS P33 Series (requires AXIS P33 Pendant Kit) AXIS P32/Q35 Series (requires AXIS T94K01D/T94M01D Pendant Kit) AXIS M3004-V/M3005-V (requires AXIS T94B01D Pendant Kit) AXIS M3006-V/M3007-P/M3007-PV (requires AXIS T94F01D Pen- dant Kit) AXIS M3024-LVE/M3025-VE/M3026-VE/M3027-PVE/M3037-PVE (r endant Kit) AXIS P3707-PE (requires AXIS T94M02D Pendant Kit) AXIS Q3709-PVE (requires AXIS T94A01D Pendant Kit) AXIS O3709-PVE (requires AXIS T94A01D Pendant Kit) AXIS O3709-PVE (requires AXIS T91A05 Camera Holder 1.5" NPS)	Approvals	Back: Cable conduit hole 3/4" IEC/EN/UL 60950-1 IEC/EN/UL 60950-22 EN 50581 IEC/EN 62262 IK10 NEMA 250 Type 4X ^a
		Dimensions	Length: 104 mm (4 in)
		Weight equires AXIS T94F02I Included	DP- Installation Guide
		accessories Optional accessories	AXIS T91B52 Extension Pipe 30 cm (12 in), AXIS T91B52 Extension Pipe 100 cm (40 in) For more accessories, see www.axis.com
Casing	Powder coated aluminum NEMA 4X-rated ^a , IK10 impact-resistant	Warranty	3-year warranty, see axis.com/warranty
Environment	Indoor Outdoor	a. Corrosion protection	
Maximum load	10 kg (22 lb)	Environmental responsibility:	
Pivot angle	±45°	axis.com/environmental-responsibility	

