

Printing date 02.09.2016 V - 4 Revision: 02.09.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Bikecare Motorcycle Garage Corrosion-Protection
- · Article number: 55120001150
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Void
- · Application of the substance / the mixture Maintenance product
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Polo Motorrad und Sportswear GmbH

Polostraße 1 D - 41363 Jüchen

Tel.: +49 2165 / 8440-200 Fax: +49 2165 / 8440-444 www.polo-motorrad.de info@polo-motorrad.com

- · Further information obtainable from: Zentrale, erreichbar werktags zwischen 8°° 19°° Uhr
- 1.4 Emergency telephone number: +49 2165 / 8440-200

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms GHS02, GHS07, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrodesulfurized heavy

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 1)

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Fatty acids, tall-oil, reaction products with boric acid (H3BO3) and diethanolamine. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of the substances with nonhazardous additions.

· Dangerous components:		
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	25-50%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-XXXX	 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 	
CAS: 106-97-8	butane	10-<20%
EINECS: 203-448-7	🚸 Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 74-98-6	propane	10-<20%
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 91770-03-5	Fatty acids, tall-oil, reaction products with boric acid (H3BO3)	<7%
EINECS: 294-785-9	and diethanolamine	
Reg.nr.: 01-2119961359-26-xxxx	♦ Skin Sens. 1B, H317	
CAS: 28016-00-4	Zinkbis-(dinonylnaphtalinsulfonat)	3-5%
Reg.nr.: 28016-00-4248-778-2	🕦 Skin Irrit. 2, H315; Eye Irrit. 2, H319	

· SVHC None

· Additional information:

EINECS: 294-785-9 specific concentration limit.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Take affected persons out into the fresh air.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

- · After skin contact: After contact with skin, wash immediately with plenty of soap and water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Hazards If swallowed or in case of vomiting, danger of entering the lungs.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

– E



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 2)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

Fire-extinguishing powder

Carbon dioxide

Water haze

Foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Danger of bursting.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid contact with skin and eyes.

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

(Contd. on page 4)



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs					
64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy					
Oral	DNEL system. effects (long-term)	26 mg/kg KG/Tag (Consumer)			
Dermal	DNEL system. effects (long-term)	26 mg/kg KG/Tag (Consumer)			
		44 mg/kg KG/Tag (Worker)			
Inhalative	DNEL system. effects (long-term)	71 mg/m³ (Consumer)			
		330 mg/m³ (Worker)			

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure good ventilation/exhaustion at the workplace.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended. After each cleaning use treatment creams, for very dry skin greasy ointments.

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Light brown
Odour: Characteristic
Odour threshold: Not determined

· **pH-value:** Void

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

• Flash point: -97 °C

· Ignition temperature: 365 °C

· **Self-igniting:** Product is not selfigniting.

(Contd. on page 5)



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 4) Danger of explosion: In use, may form flammable/explosive vapour-air mixture. · Explosion limits: Lower: 1.5 Vol % 10,9 Vol % Upper: · Vapour pressure at 20 °C: 8300 hPa · Density: Not determined. · Solubility in / Miscibility with water: Not miscible or difficult to mix. · Viscosity: Dynamic: Not determined Kinematic: Not determined 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- · 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Store away from oxidising agents.
- 10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met

Troute textory Bused on available data, the statement of the first met.				
· LD/LC50 values relevant for classification:				
64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy				
Oral	LD50	> 15000 mg/kg (rat) (OECD 401)		
Dermal	LD50	3400 mg/kg (rat) (OECD 402)		
106-97-8	106-97-8 butane			
Inhalative	LC50/4 h	658 mg/l (rat)		
28016-00-	28016-00-4 Zinkbis-(dinonylnaphtalinsulfonat)			
Oral	LD50	>2000 mg/kg (rat)		
Dermal	LD50	>20000 mg/kg (rabbit)		

- Specific symptoms in biological assay: Not determined
- · Primary irritant effect:
- Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: Vapours may cause drowsiness and dizziness.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 5)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

LC50/96h | 10-30 mg/l (oncorhynchus mykiss) (OECD 203) EC50/72h | 4,6-10 mg/l (Pseudokirchneriella subcapitata) EC50/48h | 10-22 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations.
- · European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR	1950 AEROSOLS. ENVIRONMENTALLY HAZARDOUS
·IMDG	AEROSOLS (Naphtha (petroleum), hydrodesulfurized
·IATA	heavy), MARÌNE POLLÜTANT AEROSOLS, flammable

(Contd. on page 7)



Trade name: Bikecare Motorcycle Garage Corrosion-Protection

	(Contd. of page
14.3 Transport hazard class(es)	
ADR Class Label	2 5F Gases. 2.1
IMDG, IATA Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrodesulfurized heavy
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Warning: Gases F-D,S-U SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 8)



Printing date 02.09.2016 V - 4 Revision: 02.09.2016

Trade name: Bikecare Motorcycle Garage Corrosion-Protection

(Contd. of page 7)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

EU