

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 34000038
Print date: 14.06.2016
Version: 2.0

Bike Care Wax-Spray 250 ml
Revision date: 14.06.2016
Issue date: 14.06.2016

EN
Page 1 / 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 34000038
Identification of the substance or mixture: Bike Care Wax-Spray 250 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:
wax care spray for leather

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

POLO Motorrad und Sportswear GmbH

Polostr. 1

D-41363 Jüchen

Telephone: +49 21 65/84 40-200

Telefax: +49 21 65/84 40-200

E-mail info@polo-motorrad.com

Dept. responsible for information:

E-mail (competent person) info@polo-motorrad.com

1.4. Emergency telephone number

111 (England, Wales, Scotland)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Aerosol 1 / H222

Aerosol

Extremely flammable aerosol.

Aerosol 1 / H229

Aerosol

Pressurised container: May burst if heated.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read label before use.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P273

Avoid release to the environment.

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P271

Use only outdoors or in a well-ventilated area.

P260

Do not breathe spray.

contains:

Hydrocarbons, C4,1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated hydrocarbons, C10-C12, iso alkanes, <2% aromatics

Supplemental Hazard information (EU)

EUH066

Repeated exposure may cause skin dryness or cracking.

EUH208

Contains zirconium tetrabutanolate. May produce an allergic reaction.

2.3. Other hazards

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 2 / 7

Caution/Important note: Inhalation may be damaging to health. Use only outdoors or in a well ventilated area. Spray for just a few seconds. Spray larger leather products or textiles outdoors only and allow to air-dry thoroughly. Keep away from children!

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| EC No. CAS No. INDEX No. | REACH No. Chemical name classification: | Wt % Remark |
|---------------------------------------|---|----------------|
| 297-629-8 93685-81-5 | Hydrocarbons, C4,1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Aquatic Chronic 4 H413 | 25 - 50 |
| 203-448-7 106-97-8 601-004-00-0 | 01-2119474691-32 butane compressed gas H280 / Flam. Gas 1 H220 | 25 - 50 |
| 923-037-2 | 01-2119471991-29 hydrocarbons, C10-C12, iso alkanes, <2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 | 12,5 - 20 |
| 200-827-9 74-98-6 601-003-00-5 | 01-2119486944-21 propane compressed gas H280 / Flam. Gas 1 H220 | 5 - 10 |
| 200-857-2 75-28-5 601-004-00-0 | 01-2119485395-27 isobutane compressed gas H280 / Flam. Gas 1 H220 | 1 - 2,5 |
| 213-995-3 1071-76-7 | zirconium tetrabutanolate Eye Irrit. 2 H319 / Skin Sens. 1 H317 | < 0,5 |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 3 / 7

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. **Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. **Advice for firefighters**

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. **Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. **Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. **Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. **Precautions for safe handling**

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. **Conditions for safe storage, including any incompatibilities**

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use. Read label before use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Occupational exposure limit values:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 4 / 7

butane

INDEX No. 601-004-00-0 / EC No. 203-448-7 / CAS No. 106-97-8

WEL, TWA: 1450 mg/m³; 600 ppm

WEL, STEL: 1810 mg/m³; 750 ppm

Remark: (Carc, only applies if Butane contains more than 0.1% of buta-1,3-diene)

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Recommended Respiratory protection: Respiratory protective device with half mask filter material type A. The standards EN 136, 140 and 405 of the European Commission for Standardization (CEN) make recommendations to respirators, the standards EN 149 and EN 143 provide recommendations to respiratory filters.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber) / Butyl caoutchouc (butyl rubber)

Thickness of the glove material \geq 0,7 mm

Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour: colourless

Odour: like organic solvents

| Safety relevant basis data | Unit | Method | Remark |
|-----------------------------|------------------------|--------------------|--------|
| Flash point: | -60 °C | DIN 51755 part 1 | |
| Ignition temperature in °C: | 200 °C | | |
| Lower explosion limit: | 1,2 Vol-% | | |
| Upper explosion limit: | 10,8 Vol-% | | |
| Vapour pressure at 20 °C: | 1272,42 mbar | | |
| Density at 20 °C: | 0,78 g/cm ³ | DIN EN ISO 15212-1 | |
| Water solubility (g/L): | insoluble | | |
| pH at 20 °C: | - | | |
| Viscosity at 20 °C: | < 10 mPa·s | DIN 53019 | |

9.2. Other information

Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 5 / 7

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

hydrocarbons, C10-C12, iso alkanes, <2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 5 mg/L (4 h)

Method: OECD 403

Hydrocarbons, C4,1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated

oral, LD50, Rat: > 15000 mg/kg

dermal, LD50, Rat: > 5000 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself.

SECTION 12: Ecological information

overall evaluation

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 6 / 7

There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

hydrocarbons, C10-C12, iso alkanes, <2% aromatics
Daphnia toxicity, EL0, Daphnia magna (Big water flea): 1000 mg/L (48 h)
, EL0, Pseudokirchneriella subcapitata: 1000 mg/L (72 h)
, NOELR, Pseudokirchneriella subcapitata: 1000 mg/L (72 h)
Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout): 1000 mg/L (96 h)
Hydrocarbons, C4,1,3-butadiene-free, polymd., triisobutylene fraction, hydrogenated
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 0,04 mg/L (48 h)

Long-term Ecotoxicity

hydrocarbons, C10-C12, iso alkanes, <2% aromatics
Daphnia toxicity, NOELR, Daphnia magna (Big water flea): < 1 mg/L (21 d)

12.2. Persistence and degradability

hydrocarbons, C10-C12, iso alkanes, <2% aromatics
: 31,3 % (28 d); evaluation Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

190208 liquid combustible wastes containing dangerous substances
150104 metallic packaging

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID): Aerosols, flammable
Sea transport (IMDG): AEROSOLS
Air transport (ICAO-TI / IATA-DGR): Aerosols, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

n.a.

14.5. Environmental hazards

Land transport (ADR/RID) n.a.
Marine pollutant n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 34000038 Bike Care Wax-Spray 250 ml
Print date: 14.06.2016 Revision date: 14.06.2016
Version: 2.0 Issue date: 14.06.2016

EN
Page 7 / 7

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code D

Sea transport (IMDG)

EmS-No. F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

VOC Switzerland:

weight fraction in % 88,00

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

| | | |
|--------------------------|--------------------------------------|---|
| Flam. Liq. 3 / H226 | flammable liquids | Flammable liquid and vapour. |
| Asp. Tox. 1 / H304 | Aspiration hazard | May be fatal if swallowed and enters airways. |
| Aquatic Chronic 4 / H413 | Hazardous to the aquatic environment | May cause long lasting harmful effects to aquatic life. |
| compressed gas / H280 | Gases under pressure | Contains gas under pressure; may explode if heated. |
| Flam. Gas 1 / H220 | Flammable gases | Extremely flammable gas. |
| Aquatic Chronic 2 / H411 | Hazardous to the aquatic environment | Toxic to aquatic life with long lasting effects. |
| Eye Irrit. 2 / H319 | Serious eye damage/eye irritation | Causes serious eye irritation. |
| Skin Sens. 1 / H317 | respiratory or skin sensitisation | May cause an allergic skin reaction. |

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.