

| | POSIBILIDAD DE ALTA PROFUNDIDAD | | | POSIBILIDAD DE ALTA PROFUNDIDAD | | |
|-------------------|---|---------------------------------------|---------------------------------------|---------------------------------------|---|--|
| | | | | | | |
| REFEJ PRECIO | 1190€ SI COMBO | 1190€ COMBO | 990€ SI COMBO | 990€ COMBO | 990€ SI COMBO | |
| DISPLAY | 10.4" | 10.4" | 8" | 8" | 7" | |
| RESOLUCION | 600V x 800H | 600V x 800H | 480V x 800H | 480V x 800H | 480V x 800H | |
| TIPO PANTALLA | Color TFT | Color TFT | Color TFT | Color TFT | Color TFT | |
| COLOR / BN | 65.000 Colores | 65.000 Colores | 65.000 Colores | 65.000 Colores | 65.000 Colores | |
| SONAR | HD Side Imaging HD Down Imaging DualBeam Plus | DualBeam Plus | DualBeam Plus | DualBeam Plus | HD Side Imaging HD Down Imaging DualBeam Plus | |
| COBERTURAS | 20° / 60° @ 100b 300/83/450/90 kHz | 20° / 60° @ 100b 300/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | |
| POTENCIA SALIDA | 100W RMS 8300W PTP | 100W RMS 8300W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP | |
| CONSUMO CORRIENTE | 1.5mA | 1.5mA | 790mA | 790mA | 790mA | |
| TEMPERATURA | Si | Si | Si | Si | Si | |
| VELOCIDAD | GPS incluido | GPS incluido | GPS incluido | GPS incluido | GPS incluido | |
| RETROILUMINACION | Si | Si | Si | Si | Si | |
| TRANSDUCTOR | XHS-9-HDS-180-T | XMT-9-20-T | XHS-9-HDS-180-T | XMT-9-20-T | XHS-9-HDS-180-T | |

| | POSIBILIDAD DE ALTA PROFUNDIDAD | | ALTA PROFUNDIDAD INCORPORADA | | ALTA PROFUNDIDAD INCORPORADA | |
|-------------------|---------------------------------------|---|---------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| | | | | | | |
| REFEJ PRECIO | 950€ COMBO | 790€ SI COMBO | 790€ SI COMBO | 790€ SI COMBO | 790€ SI COMBO | 790€ SI COMBO |
| DISPLAY | 7" | 5" | 5" | 5" | 5" | 5" |
| RESOLUCION | 480V x 800H | 640V x 640H | 640V x 640H | 640V x 640H | 640V x 640H | 640V x 640H |
| TIPO PANTALLA | Color TFT | Color TFT | Color TFT | Color TFT | Color TFT | Color TFT |
| COLOR / BN | 65.000 Colores | 256 | 256 | 256 | 256 | 256 |
| SONAR | DualBeam PLUS | Side Imaging Down Imaging DualBeam Plus | Down Imaging DualBeam Plus | Down Imaging DualBeam Plus | Down Imaging DualBeam Plus | Down Imaging DualBeam Plus |
| COBERTURAS | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz |
| POTENCIA SALIDA | 100W RMS 8000W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP | 100W RMS 8000W PTP |
| CONSUMO CORRIENTE | 790mA | 615mA | 615mA | 615mA | 615mA | 615mA |
| TEMPERATURA | Si | Si | Si | Si | Si | Si |
| VELOCIDAD | GPS incluido | GPS incluido | Si | GPS incluido | GPS incluido | Disponible |
| RETROILUMINACION | Si | Si | Si | Si | Si | Si |
| TRANSDUCTOR | XMT-9-20-T | XNT-9-SI-180-T | XNT-9-SI-180-T | XNT-9-DB-74-T | XNT-9-20-T | XNT-9-20-T |

| | ALTA PROFUNDIDAD INCORPORADA | | | | |
|-------------------|---------------------------------------|---|---------------------------------------|---|---------------------------------------|
| | | | | | |
| REFEJ PRECIO | 718€ | 897€ SI COMBO | 897€ SI COMBO | 897€ SI COMBO | 897€ SI COMBO |
| DISPLAY | 5" | 5" | 5" | 5" | 4.5" |
| RESOLUCION | 320V x 200H | 640V x 640H | 640V x 640H | 640V x 640H | 640V x 450H |
| TIPO PANTALLA | FS1N LCD | Color TFT | Color TFT | Color TFT | Color TFT |
| COLOR / BN | 16 Niveles de Gris | 16 Niveles de Gris | 256 | 256 | 256 |
| SONAR | DualBeam Plus | DualBeam Plus | DualBeam Plus | DualBeam Plus | DualBeam Plus |
| COBERTURAS | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 74° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 16° 75° 25° 45° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz |
| POTENCIA | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP |
| CONSUMO CORRIENTE | 200mA | 615mA | 615mA | 615mA | 615mA |
| TEMPERATURA | Si | Si | Si | Si | Si |
| VELOCIDAD | Disponible | Si | GPS incluido | Disponible | GPS incluido |
| RETROILUMINACION | Si | Si | Si | Si | Si |
| TRANSDUCTOR | XNT-9-20-T | XMT-DB-74-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T |

| | ALTA PROFUNDIDAD INCORPORADA | | | | | | | | | |
|-------------------|---------------------------------------|---|---------------------------------------|---------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|--|--|--|
| | | | | | | | | | | |
| REFEJ PRECIO | 696€ SI COMBO | 570€ SI COMBO | 570€ | 561€ | 385 COMBO | 360 COMBO | 340€ | | | |
| DISPLAY | 4.5" | 5" | 5" | 5" | 3.5" | 4" | 3.5" | | | |
| RESOLUCION | 640V x 480H | 640V x 320H | 640V x 320H | 320V x 240H | 320V x 240H | 320V x 240H | 320V x 240H | | | |
| TIPO PANTALLA | Color TFT | FS1N LCD | FS1N LCD | FS1N LCD | Color TFT | FS1N LCD | Color TFT | | | |
| COLOR / BN | 256 | 16 Niveles de Gris | 12 Niveles de Gris | 12 Niveles de Gris | 256 | 16 Niveles de Gris | 256 | | | |
| SONAR | DualBeam Plus | Down Imaging DualBeam Plus | DualBeam Plus | Single Beam | DualBeam Plus | DualBeam Plus | DualBeam Plus | | | |
| COBERTURAS | 20° x 60° @ 100b 200/83/450/90 kHz | 16° 75° 25° 45° @ 100b 200/83/450/90 kHz | 20° @ 60° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | | | |
| POTENCIA | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | | | |
| CONSUMO CORRIENTE | 615mA | 200mA | 200mA | 200mA | 200mA | 380mA | 270mA | | | |
| TEMPERATURA | Si | Si | Si | Si | Si | Si | Si | | | |
| VELOCIDAD | Disponible | Disponible | Disponible | Disponible | Disponible | GPS incluido | Disponible | | | |
| RETROILUMINACION | Si | Si | Si | Si | Si | Si | Si | | | |
| TRANSDUCTOR | XNT-9-DB-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | | | |

| | ALTA PROFUNDIDAD INCORPORADA | | | | |
|-------------------|---------------------------------------|---------------------------------|---------------------------------------|---------------------------------|---------------------------------|
| | | | | | |
| REFEJ PRECIO | NS-325X | NS-325X | NS-325X | NS-325X | NS-325X |
| DISPLAY | 4" | 1.5" | 3.5" | 4" | 4" |
| RESOLUCION | 320V x 240H | 320V x 240H | 320V x 240H | 320V x 240H | 320V x 240H |
| TIPO PANTALLA | FS1N LCD | LCD | Color TFT | FS1N LCD | FS1N LCD |
| COLOR / BN | 16 Niveles de gris | - | 256 | 8 Niveles de gris | 4 Niveles de gris |
| SONAR | DualBeam Plus | Single Beam | SingleBeam | DualBeam | SingleBeam |
| COBERTURAS | 20° / 60° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz |
| POTENCIA | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP |
| CONSUMO CORRIENTE | 270mA | - | 220mA | 100mA | 800mA |
| TEMPERATURA | Si | - | Si | Si | Si |
| VELOCIDAD | Disponible | - | Si | - | - |
| RETROILUMINACION | Si | Si | Si | Si | Si |
| TRANSDUCTOR | - | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T |

| | ALTA PROFUNDIDAD INCORPORADA | | | | | | | | | |
|-------------------|---------------------------------------|---------------------------------|---|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|--|--|
| | | | | | | | | | | |
| REFEJ PRECIO | 47€ | 47€ | - | 13€ | 13€ | 13€ | 13€ | | | |
| RESOLUCION | 480V x 160H | 160V x 120H | - | 480V x 320H | 160V x 120H | 480V x 320H | 480V x 320H | | | |
| TIPO PANTALLA | FS1N LCD | FS1N LCD | - | FS1N LCD | FS1N LCD | FS1N LCD | FS1N LCD | | | |
| COLOR / BN | 8 Niveles de gris | 4 Niveles de gris | - | - | - | - | 4 Niveles de gris | | | |
| SONAR | SingleBeam | SingleBeam Down | - | SingleBeam | SingleBeam | SingleBeam | SingleBeam | | | |
| COBERTURAS | 34° x 10° @ 100b 200/83/450/90 kHz | 34° @ 100b 200/83/450/90 kHz | - | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | | | |
| POTENCIA | 125W RMS 800W PTP | 100W RMS 800W PTP | - | 100W RMS 800W PTP | 100W RMS 800W PTP | 100W RMS 800W PTP | 100W RMS 800W PTP | | | |
| CONSUMO CORRIENTE | 110mA | 100mA | - | - | - | - | - | | | |
| TEMPERATURA | Si | Si | - | Si | Si | Si | Si | | | |
| VELOCIDAD | - | - | - | - | - | - | - | | | |
| RETROILUMINACION | Si | Si | - | Si | Si | Si | Si | | | |
| TRANSDUCTOR | 24" Mast | 24" Mast | - | - | - | - | - | | | |

| | ALTA PROFUNDIDAD INCORPORADA | | | | |
|-------------------|---------------------------------------|---------------------------------|---------------------------------------|---------------------------------|---------------------------------|
| | | | | | |
| REFEJ PRECIO | NS-330 | NS-373 | NS-324 | NS-311 | NS-323 |
| DISPLAY | 4" | 1.5" | 3.5" | 4" | 4" |
| RESOLUCION | 320V x 240H | 320V x 240H | 320V x 240H | 320V x 240H | 320V x 240H |
| TIPO PANTALLA | FS1N LCD | LCD | Color TFT | FS1N LCD | FS1N LCD |
| COLOR / BN | 16 Niveles de gris | - | 256 | 8 Niveles de gris | 4 Niveles de gris |
| SONAR | DualBeam Plus | Single Beam | SingleBeam | DualBeam | SingleBeam |
| COBERTURAS | 20° / 60° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz | 20° / 60° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz | 20° @ 100b 200/83/450/90 kHz |
| POTENCIA | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP | 100W RMS 4000W PTP |
| CONSUMO CORRIENTE | 270mA | - | 220mA | 100mA | 800mA |
| TEMPERATURA | Si | - | Si | Si | Si |
| VELOCIDAD | Disponible | - | Si | - | - |
| RETROILUMINACION | Si | Si | Si | Si | Si |
| TRANSDUCTOR | - | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T | XNT-9-20-T |

| | ALTA PROFUNDIDAD INCORPORADA | | | | | | | | | |
|-------------------|---------------------------------------|---------------------------------|---|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|--|--|
| | | | | | | | | | | |
| REFEJ PRECIO | 47€ | 47€ | - | 13€ | 13€ | 13€ | 13€ | | | |
| RESOLUCION | 480V x 160H | 160V x 120H | - | 480V x 320H | 160V x 120H | 480V x 320H | 480V x 320H | | | |
| TIPO PANTALLA | FS1N LCD | FS1N LCD | - | FS1N LCD | FS1N LCD | FS1N LCD | FS1N LCD | | | |
| COLOR / BN | 8 Niveles de gris | 4 Niveles de gris | - | - | - | - | 4 Niveles de gris | | | |
| SONAR | SingleBeam | SingleBeam Down | - | SingleBeam | SingleBeam | SingleBeam | SingleBeam | | | |
| COBERTURAS | 34° x 10° @ 100b 200/83/450/90 kHz | 34° @ 100b 200/83/450/90 kHz | - | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | 90° @ 100b 200/83/450/90 kHz | | | |
| POTENCIA | 125W RMS 800W PTP | 100W RMS 800W PTP | - | 100W RMS 800W PTP | 100W RMS 800W PTP | 100W RMS 800W PTP | 100W RMS 800W PTP | | | |
| CONSUMO CORRIENTE | 110mA | 100mA | - | - | - | - | - | | | |
| TEMPERATURA | Si | Si | - | Si | Si | Si | Si | | | |
| VELOCIDAD | - | - | - | - | - | - | - | | | |
| RETROILUMINACION | Si | Si | - | Si | Si | Si | Si | | | |
| TRANSDUCTOR | 24" Mast | 24" Mast | - | - | - | - | - | | | |