

Display Size - Diagonal: 7"
Display Pixel Matrix: 800H x 480V
Display Type: Color TFT
Display Colors Grayscale: 256 Colors
Sonar Standard: DualBeam PLUS
Standard Sonar Coverage: 20° & 60° @ -10db
Standard Sonar Frequency: 200/83 kHz
Target Separation: 2.5"
Power Output RMS: 500 Watts
Power Output Peak to Peak: 4000 Watts
Depth Capability: 1500 ft
Temperature: Built In Transducer
Speed: GPS Speed Included
Backlight: LED
Unit Size - Gimbal Mount: 10.54"W x 5.44"H x 1.13"D
Mount A Type: Gimbal Mount
Unit Size - Indash Mount: 10.54"W x 5.80"H x 3.68"D
Mount B Unit Size2: Optional In-Dash
Mounting Options: Gimbal or Optional In-Dash
Transducer Standard: XNT 9 20 T
Transducer Mounting: Transom
Power Input: 10-20 VDC
Power Draw: 800 mA
GPS Receiver: Included
GPS Tracking: Included
GPS Chartplotting: Included
Waypoints, Routes, Tracks/Points: 2,500, 45, 50/20,000
Humminbird Mapping: Optional
Navionics Gold/HotMaps: Optional
Navionics Platinum+: Not Supported
Platinum Capable: Not Supported
C-Map 4D: Not Supported
360 Imaging: Not Supported
i-Pilot Link: Not Supported
HD Radar: Not Supported
NMEA 2000: Not Supported
5 Port Expansion Module: Not Supported
WeatherSense: Not Supported

Precision GPS: Included
Heading Sensor GPS: Not Supported
PC Connect: Optional
External GPS Receiver: Not Supported
AS Interlink: Not Supported
AIS Compatability: Not Supported
SwitchFire Sonar: Included
Screen Snap Shot: Included
Sonar Recording: Included
Upgradable Internal Software: Included
Split Screen Zoom: Included
Split Screen Bottom Lock: Included
3D Chart View: Included
Large Digits View: Included
Wide/Narrow Cone Split Screen: Included
Custom View Selections: Included
Custom Digital Readout: Included
View Preset Keys: Not Supported
Temperature Graph: Not Supported
Temperature Alarm: Included
Freeze Frame: Included
Instant Image Update: Included
Mark Structure on Sonar: Included
Selective Fish ID+: Included
Real Time Sonar: Included
Triplot: Included
X-Press Menu System: Included
Card Reader Available: Yes
Card Slots: 1
Domestic CHO: no
Intl Portable: no
Hardware: MHX XNTF
Transducer 2: XNT 9 20 T
Bronze Thru Hull: XTH 9 20
Plastic Thru Hull: XTH 9 20 P
Puck: XP 9 20 T
Trolling Motor: XTM 9 20 T
Angled Puck: XAP 9 20
Portable 2: XPT 9 20 T
Bronze 3-n-1: N/A