

Overview	
Display	Widescreen, 16:9 ; WVGA color TFT LCD
Resolution	800 x 480
Power Output: RMS (PTP)	Max 500W RMS
Operating Frequency	(50/200 or 83/200 kHz) + 455/800 kHz
Languages	36
Media Port	1 SD (full size)
Warranty	Two Year
Display	
Display Resolution	800 x 480
Display Type	WVGA color TFT LCD
GPS and Sonar Overlay Data	Yes
Split Screen Presentation	4
Display Size	7"/ 178 mm
Brightness	1250 nits
Sonar	
Depth Alarm	Yes
Shallow Alarm	Yes
Standard Fishfinding Features: COLORLINE™ or GRAYLINE®, ASP™, FishSymbol I.D.™, FishTrack™, and more	Yes
Temperature Readings	Yes
Transducer Type	Multiple Selections Lowrance and Airmar
Technical/Environmental	
Operating Temperature	-15° C to + 55° C (+ 5° F to + 131° F)
Product Width	8.44"
Product Depth	3.24"
Product Height	5.76"
Power	
Power Consumption	12 W (0.9 A @ 13 V DC)
Power Supply (Supply Voltage)	12 V DC (10.8 - 17.0 V DC min - max) 31
GPS Navigation	
Navigation: Routes	200
Navigation: Waypoint Storage	5000
GPS Alarms	Yes
Background Mapping	Built in Insight USA™ (Americas) or Worldwide background map (non-Americas)
Other	
Languages	36 total, available on 5 Language Packs