

**Cinturato™ VELO**

# PURE PROTECTION



**Cinturato Velo** is the new tubeless-ready clincher tyre from Pirelli, crafted around protection and comfort, without compromising performances.





## KEY FEATURES

Pirelli's **experience** and the reliability of **SmartNET™ Silica** technology combined with the tubeless-ready comfort and the resistance of the **Armour Tech™** technology facilitated the creation of a new clincher tyre with a unique DNA, perfect for long-distances and various terrains.

**Armour Tech™** construction (patent pending) combines various components, in order from inside to outside, which add to the 60 TPI Nylon casing underneath:

- high density **Nylon layer** from bead to bead, which protects against cuts as well as improved stability at low pressure riding and contribute to make the carcass air tight when used with liquid sealant
  - high density waved **aramid fiber breaker** belt placed underneath the tread, which provides protection against punctured and sharp object cuts
  - **aramid fibrils** dispersed into the tread rubber compound (SmartNET™ Silica) in two layers: an outer one (cap) which grants performances (dry & wet, mileage, contact feeling), an inner one (base) which, thanks to an higher gradient of those fibrils, slows down the penetration of foreign bodies towards underneath layers

# TECHNICAL SPECIFICATION

DESCRIPTION	SIZE	WEIGHT	CASING	PROTECTION	TREAD	BEAD	COMPATIBILITY
<b>Cinturato™ VELO</b>	26-622	290g	60 tpi Nylon	 armour tech™	<b>SMARTNET™ SILICA™</b> (Cap & Base)	Aramid TLR	Do not fit on TSS (Hook-Less) rims or if inner rim width is greater than 19C
<b>Cinturato™ VELO</b>	28-622	320g	60 tpi Nylon	 armour tech™	<b>SMARTNET™ SILICA™</b> (Cap & Base)	Aramid TLR	Do not fit on TSS (Hook-Less) rims or if inner rim width is greater than 20C
<b>Cinturato™ VELO</b>	32-622	350g	60 tpi Nylon	 armour tech™	<b>SMARTNET™ SILICA™</b> (Cap & Base)	Aramid TLR	Do not fit on TSS (Hook-Less) rims or if inner rim width is greater than 21C
<b>Cinturato™ VELO</b>	35-622	380g	60 tpi Nylon	 armour tech™	<b>SMARTNET™ SILICA™</b> (Cap & Base)	Aramid TLR	Do not fit on TSS (Hook-Less) rims or if inner rim width is greater than 24C

## FEATURED TECHNOLOGY



### TUBELESS-READY & TUBETYPE

The bead of the Cinturato Velo has been designed to maximize compatibility and air-tight with tubeless-ready rims, as well as easy mounting in either tube type or tubeless-ready configurations.

