

RECOMMENDED PRESSURES - ROAD

P ZERO™ VELO

23-622 700x23c		25-622 700x25c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 51 kg ≤ 112 lbs	6,7 bar 95 psi	≤ 48 kg ≤ 106 lbs	6 bar 85 psi	≤ 65 kg ≤ 143 lbs	6 bar 85 psi
52 > 60 kg 113 > 133 lbs	7 bar 100 psi	49 > 56 kg 107 > 123 lbs	6,3 bar 90 psi	66 > 78 kg 144 > 172 lbs	6,3 bar 90 psi
61 > 68 kg 134 > 150 lbs	7,3 bar 105 psi	57 > 63 kg 124 > 139 lbs	6,7 bar 95 psi	79 > 89 kg 173 > 196 lbs	6,7 bar 95 psi
69 > 76 kg 151 > 168 lbs	7,7 bar 110 psi	64 > 72 kg 140 > 159 lbs	7 bar 100 psi	90 > 103 kg 197 > 227 lbs	7 bar 100 psi
77 > 84 kg 169 > 185 lbs	8 bar 115 psi	73 > 86 kg 160 > 190 lbs	7,3 bar 105 psi	104 > 120 kg 228 > 265 lbs	7,3 bar 105 psi
85 > 92 kg 186 > 203 lbs	8,3 bar 120 psi	≥ 87 kg ≥ 191 lbs	7,7 bar 110 psi	≥ 121 kg ≥ 266 lbs	7,7 bar 110 psi
≥ 93 kg ≥ 204 lbs	8,7 bar 125 psi				

Cinturato™ VELO TUBE TYPE

26-622 700x26c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 52 kg ≤ 115 lbs	5,6 bar 80 psi	≤ 53 kg ≤ 117 lbs	4,9 bar 70 psi
53 > 61 kg 116 > 134 lbs	6 bar 85 psi	54 > 60 kg 118 > 132 lbs	5,3 bar 75 psi
62 > 74 kg 135 > 163 lbs	6,3 bar 90 psi	61 > 68 kg 133 > 150 lbs	5,6 bar 80 psi
75 > 90 kg 164 > 198 lbs	6,7 bar 95 psi	69 > 79 kg 151 > 174 lbs	6 bar 85 psi
91 > 108 kg 199 > 238 lbs	7 bar 100 psi	80 > 89 kg 175 > 196 lbs	6,3 bar 90 psi
≥ 109 kg ≥ 239 lbs	7,4 bar 105 psi	90 > 98 kg 197 > 216 lbs	6,7 bar 95 psi
		≥ 99 kg ≥ 217 lbs	7 bar 100 psi

Cinturato™ VELO TUBELESS READY

26-622 700x26c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 44 kg ≤ 97 lbs	4,7 bar 65 psi	≤ 48 kg ≤ 106 lbs	4,3 bar 60 psi
45 > 53 kg 98 > 117 lbs	5 bar 70 psi	49 > 55 kg 107 > 121 lbs	4,7 bar 65 psi
54 > 63 kg 118 > 139 lbs	5,3 bar 75 psi	56 > 63 kg 122 > 139 lbs	5 bar 70 psi
64 > 76 kg 140 > 168 lbs	5,7 bar 80 psi	64 > 74 kg 140 > 163 lbs	5,3 bar 75 psi
≥ 77 kg ≥ 169 lbs	6 bar 85 psi	75 > 85 kg 164 > 187 lbs	5,7 bar 80 psi
		≥ 86 kg ≥ 188 lbs	6 bar 85 psi

Depending on riding style and/or rider's position on the bike:

- confort > drop 0,3 bar / 5 psi on FRONT wheel

- aggressive > keep same pressure front and rear

If wet and/or cold road conditions (below 7° C) drop 0.3 bar / 5 psi on BOTH wheels



RECOMMENDED PRESSURES - ROAD

P ZERO™ VELO					
23-622 700x23c		25-622 700x25c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 51 kg ≤ 112 lbs	6,7 bar 95 psi	≤ 48 kg ≤ 106 lbs	6 bar 85 psi	≤ 65 kg ≤ 143 lbs	6 bar 85 psi
52 > 60 kg 113 > 133 lbs	7 bar 100 psi	49 > 56 kg 107 > 123 lbs	6,3 bar 90 psi	66 > 78 kg 144 > 172 lbs	6,3 bar 90 psi
61 > 68 kg 134 > 150 lbs	7,3 bar 105 psi	57 > 63 kg 124 > 139 lbs	6,7 bar 95 psi	79 > 89 kg 173 > 196 lbs	6,7 bar 95 psi
69 > 76 kg 151 > 168 lbs	7,7 bar 110 psi	64 > 72 kg 140 > 159 lbs	7 bar 100 psi	90 > 103 kg 197 > 227 lbs	7 bar 100 psi
77 > 84 kg 169 > 185 lbs	8 bar 115 psi	73 > 86 kg 160 > 190 lbs	7,3 bar 105 psi	104 > 120 kg 228 > 265 lbs	7,3 bar 105 psi
85 > 92 kg 186 > 203 lbs	8,3 bar 120 psi	≥ 87 kg ≥ 191 lbs	7,7 bar 110 psi	≥ 121 kg ≥ 266 lbs	7,7 bar 110 psi
≥ 93 kg ≥ 204 lbs	8,7 bar 125 psi				

Cinturato™ VELO TUBE TYPE			
26-622 700x26c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 52 kg ≤ 115 lbs	5,6 bar 80 psi	≤ 53 kg ≤ 117 lbs	4,9 bar 70 psi
53 > 61 kg 116 > 134 lbs	6 bar 85 psi	54 > 60 kg 118 > 132 lbs	5,3 bar 75 psi
62 > 74 kg 135 > 163 lbs	6,3 bar 90 psi	61 > 68 kg 133 > 150 lbs	5,6 bar 80 psi
75 > 90 kg 164 > 198 lbs	6,7 bar 95 psi	69 > 79 kg 151 > 174 lbs	6 bar 85 psi
91 > 108 kg 199 > 238 lbs	7 bar 100 psi	80 > 89 kg 175 > 196 lbs	6,3 bar 90 psi
≥ 109 kg ≥ 239 lbs	7,4 bar 105 psi	90 > 98 kg 197 > 216 lbs	6,7 bar 95 psi
		≥ 99 kg ≥ 217 lbs	7 bar 100 psi

Cinturato™ VELO TUBELESS READY			
26-622 700x26c		28-622 700x28c	
Rider weight (kg/lbs)	Pressure (bar/psi)	Rider weight (kg/lbs)	Pressure (bar/psi)
≤ 44 kg ≤ 97 lbs	4,7 bar 65 psi	≤ 48 kg ≤ 106 lbs	4,3 bar 60 psi
45 > 53 kg 98 > 117 lbs	5 bar 70 psi	49 > 55 kg 107 > 121 lbs	4,7 bar 65 psi
54 > 63 kg 118 > 139 lbs	5,3 bar 75 psi	56 > 63 kg 122 > 139 lbs	5 bar 70 psi
64 > 76 kg 140 > 168 lbs	5,7 bar 80 psi	64 > 74 kg 140 > 163 lbs	5,3 bar 75 psi
≥ 77 kg ≥ 169 lbs	6 bar 85 psi	75 > 85 kg 164 > 187 lbs	5,7 bar 80 psi
		≥ 86 kg ≥ 188 lbs	6 bar 85 psi

Depending on riding style

and/or rider's position on the bike:

- confort > drop 0,3 bar / 5 psi on FRONT wheel
 - aggressive > keep same pressure front and rear
- If wet and/or cold road conditions (below 7° C)
drop 0.3 bar / 5 psi on BOTH wheels

