

Specifications

Weight	0.32 kg (0.7 lbs)
NMEA 2000 Connectivity	1 x NMEA2000 Micro-C port, 1 LEN
Power Consumption typical	1.8W
Dimensions H x W x D	118 x 115 x 37mm (4.6 x 4.5 x 1.4")
Supply Voltage	12V DC (10-16V DC)
Warranty Period	2 Years
Power Consumption max	2.2W
Operating Temperature Range	-25 to +65°C (-13°F to +149°F)
Compass Safe	300mm (1.0')
Display Resolution	320 x 240, 4:3
Recommended Fuse Rating	3A
Storage Temperature Range	-40 to +85°C (-40°F to +185°F)
Languages	English, French, Spanish, German, Italian, Swedish, South African, Danish, Finnish, Icelandic, Dutch, Norwegian, Portugues, Greek
Mounting Type	Flush
Approvals Compliance	IEC/EN 60945
Waterproofing	IPx7
Interface	Keypad
N2K PGNs	Receive: 59392,59904,60928,126208,126992,126996,127488,127489,127505,127508,128259,128267,129025,129026,129029,129033,130136 Transmit: 59904, 60928, 126208, 126996, 127258
Humidity	Up to 95% RH
Backlight Color	White, Red, Green, Blue