

T81FC - T83NRFC (ANTI-FEEDBACK) TILT STEERING SYSTEMS



FEATURING PLANETARY GEAR DESIGN

26

A COMPLETE STEERING SYSTEM CONSISTS OF:

- Steering helm:
T81FC - 38957 J
 single cable steering helm
T83NRFC - 38959 N
 anti-feedback single cable steering helm
- Tilt mechanism:
X52 - 39250 U
NOTE: X52 tilt mechanism fits Ultraflex tilt mount rotary and rack and pinion steering helms as well as Ultraflex tilt mount hydraulic pumps except SilverSteer™ and MasterDrive™ steering systems
- Steering cable: **M66**
- Optional steering wheel (see index)
- Engine connection kits (see index)

FEATURES AND TECHNICAL SPECIFICATIONS:

- Tilt range of 48° and five locking positions
- Fast connect, simple installation
- Tilt device eliminates underdash movement
- Standard 3/4" tapered shaft - stainless steel
- All stainless steel cable output ends
- Corrosion resistant materials
- Lock-to-lock steering wheel turns:
approx. 3,8
- Stroke: 228 mm (9")
- Maximum allowable steering wheel
diameter: 406 mm (16")
- Minimum steering cable bend radius:
200 mm (7.9")
- T81FC and T83NRFC steering systems are
not to be used on boats equipped with
engines that exceed the maximum
horsepower rating of the boat
- For boats faster than 50 mph our hydraulic
steering systems are recommended
- Exceeds EN 28848 safety standards
- Exceeds ABYC P17 safety standards



T81FC with X52



X52



M66

