

Page 1 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40® Specialist® Motorbike Chain Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Universal cleaner

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom
 Phone: +44 (0) 1908 555400, Fax: +44 (0) 1908 266900
www.wd40.co.uk

IRL

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland
 Phone: 01-832 0006, Fax: 01-832 0016
web@team.ie

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
 (+353) 01 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
 (+353) 01 837 9964 or 01 809 2566 (Info for Healthcare Professionals ONLY, 24 h)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WDC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H336-May cause drowsiness or dizziness.
Aerosol	1	H222-Extremely flammable aerosol.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

Page 2 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.
 P312-Call a POISON CENTER/doctor if you feel unwell.
 P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
 P501-Dispose of contents/container safely.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
 Propan-2-ol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Danger of bursting (explosion) when heated

REGULATION (EC) No 648/2004

30 % and more
 aliphatic hydrocarbons
 less than 5 %
 non-ionic surfactants

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	---
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	---
content %	70-80
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336

Petroleum gases, liquified	
Registration number (REACH)	--
Index	649-202-00-6
EINECS, ELINCS, NLP	270-704-2
CAS	68476-85-7
content %	0,1-<29
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Gas 1, H220

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	1-5

Page 3 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

Classification according to Regulation (EC) 1272/2008 (CLP)

Flam. Liq. 2, H225
 Eye Irrit. 2, H319
 STOT SE 3, H336

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.
 Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.
 Danger of aspiration
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

with long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration

Oedema of the lungs

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2

Extinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air mixture

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Do not use on hot surfaces.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Observe special regulations for aerosols!

Store cool.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

7.3 Specific end use(s)

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.07.2015 / 0002

Replacing version dated / version: 28.11.2013 / 0001

Valid from: 10.07.2015

PDF print date: 11.08.2015

WD-40® Specialist® Motorbike Chain Cleaner

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

(GB) Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Content %:70-80
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	

(IRL) Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Content %:70-80
OELV-8h: 100 ppm (573 mg/m ³) (White Spirit)	OELV-15min: 125 ppm (720 mg/m ³) (White Spirit)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BLV: ---	Other information: ---	

(GB) Chemical Name	Petroleum gases, liquified	Content %:0,1-<29
WEL-TWA: 1000 ppm (1750 mg/m ³) (Liquefied petroleum gas (LPG))	WEL-STEL: 1250 ppm (2180 mg/m ³) (Liquefied petroleum gas (LPG))	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

(IRL) Chemical Name	Petroleum gases, liquified	Content %:0,1-<29
OELV-8h: 1000 ppm (1800 mg/m ³)	OELV-15min: 1250 ppm (2250 mg/m ³)	---
Monitoring procedures:	---	
BLV: ---	Other information: ---	

(GB) Chemical Name	Propan-2-ol	Content %:1-5
WEL-TWA: 400 ppm (999 mg/m ³)	WEL-STEL: 500 ppm (1250 mg/m ³)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - Draeger - Alcohol 25/a i-Propanol (81 01 631) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - Draeger - Alcohol 25/a (81 01 631) - Draeger - Alcohol 100/a (CH 29 701) 	
BMGV: ---	Other information: ---	

(IRL) Chemical Name	Propan-2-ol	Content %:1-5
OELV-8h: 200 ppm	OELV-15min: 400 ppm	---
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - Draeger - Alcohol 25/a i-Propanol (81 01 631) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - Draeger - Alcohol 25/a (81 01 631) - Draeger - Alcohol 100/a (CH 29 701) 	
BLV: 40 mg/l (acetone, U, d) (ACGIH-BEI)	Other information: Sk	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(IRL) OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable

Fraction. (R) = Respirable Fraction. | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol, Substance: Liquid
Colour:	Colourless
Odour:	Solvent
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	Not determined
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Possible build up of explosive/highly flammable vapour/air mixture. Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.07.2015 / 0002

Replacing version dated / version: 28.11.2013 / 0001

Valid from: 10.07.2015

PDF print date: 11.08.2015

WD-40® Specialist® Motorbike Chain Cleaner

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

WD-40® Specialist® Motorbike Chain Cleaner

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, reddening of the skin
Specific target organ toxicity - repeated exposure (STOT-RE), oral:					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Not to be expected

Petroleum gases, liquified

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	>5	mg/l			
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant

Propan-2-ol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea

SECTION 12: Ecological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.07.2015 / 0002

Replacing version dated / version: 28.11.2013 / 0001

Valid from: 10.07.2015

PDF print date: 11.08.2015

WD-40® Specialist® Motorbike Chain Cleaner

Possibly more information on environmental effects, see Section 2.1 (classification).

WD-40® Specialist® Motorbike Chain Cleaner

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer. Isolate as much as possible with an oil separator.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss		
Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOELR	21d	0,23	mg/l	Daphnia magna	QSAR	
Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	EL50	72h	>1000	mg/l	Pseudokirchnerie lla subcapitata		
Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	groth rate

Toxicity to algae:	NOELR	72h	100	mg/l	Pseudokirchnerie lla subcapitata		
Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie lla subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Petroleum gases, liquified

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Bioaccumulative potential:							No

Propan-2-ol

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	9640	mg/l	Pimephales promelas		
Toxicity to daphnia:	EC50	48h	13299	mg/l	Daphnia magna		References
Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
Toxicity to algae:	EC50	72h	>1000	mg/l	Desmodesmus subspicatus		
Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
Mobility in soil:	Koc		1,1				expert judgement
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Toxicity to bacteria:	EC10	18h	5175	mg/l	Pseudomonas putida	DIN 38412 T.8	
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	ThOD		2,4	g/g			
Water solubility:							Soluble

SECTION 13: Disposal considerations**13.1 Waste treatment methods****For the substance / mixture / residual amounts**

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Page 12 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

UN number: 1950

Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1950 AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

Classification code:

5F

LQ (ADR 2015):

1 L

Environmental hazards:

Not applicable

Tunnel restriction code:

D

Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS

Transport hazard class(es):

2.1

Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

Environmental hazards:

Not applicable

Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es):

2.1

Packing group:

-

Environmental hazards:

Not applicable

Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Directive 2010/75/EU (VOC):

99,25 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EUF0025

Revised sections:

1 - 16

Page 13 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 10.07.2015 / 0002
 Replacing version dated / version: 28.11.2013 / 0001
 Valid from: 10.07.2015
 PDF print date: 11.08.2015
 WD-40® Specialist® Motorbike Chain Cleaner

These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.
 Employee training in handling dangerous goods is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H336	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H220 Extremely flammable gas.

STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aerosol — Aerosols
 Asp. Tox. — Aspiration hazard
 Flam. Liq. — Flammable liquid
 Flam. Gas — Flammable gases (including chemically unstable gases)
 Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 10.07.2015 / 0002

Replacing version dated / version: 28.11.2013 / 0001

Valid from: 10.07.2015

PDF print date: 11.08.2015

WD-40® Specialist® Motorbike Chain Cleaner

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.