

Page 1 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **WD-40® Specialist®Motorbike Chain Wax**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### **Relevant identified uses of the substance or mixture:**

Lubricant

##### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom  
 Phone: +44 (0) 1908 555400, Fax: +44 (0) 1908 266900  
[www.wd40.co.uk](http://www.wd40.co.uk)

IRL

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland  
 Phone: 01-832 0006, Fax: 01-832 0016  
[web@team.ie](mailto:web@team.ie)

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### **Emergency information services / official advisory body:**

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
 (+353) 01 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
 (+353) 01 837 9964 or 01 809 2566 (Info for Healthcare Professionals ONLY, 24 h)

##### **Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (WDC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### **Classification according to Regulation (EC) 1272/2008 (CLP)**

| Hazard class    | Hazard category | Hazard statement                                      |
|-----------------|-----------------|---|
| Skin Irrit.     | 2               | H315-Causes skin irritation.                          |
| STOT SE         | 3               | H336-May cause drowsiness or dizziness.               |
| Aquatic Chronic | 2               | H411-Toxic to aquatic life with long lasting effects. |
| Aerosol         | 1               | H222-Extremely flammable aerosol.                     |
| Asp. Tox.       | 1               | H304-May be fatal if swallowed and enters airways.    |
| Aerosol         | 1               | H229-Pressurised container: May burst if heated.      |

#### 2.2 Label elements

##### **Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 10.07.2015 / 0003

Replaces revision of / Version: 02.09.2014 / 0002

Valid from: 10.07.2015

PDF print date: 15.07.2015

WD-40® Specialist®Motorbike Chain Wax



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTER/doctor if you feel unwell.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents/container safely.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C6, isoalkanes, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substance

n.a.

### 3.2 Mixture

|   |  |
|---|--|
| <b>Hydrocarbons, C6, isoalkanes, &lt; 5% n-hexane</b>       |  |
| Registration number (REACH)                                 | 01-2119484651-34-XXXX  |
| Index   | ---  |
| EINECS, ELINCS, NLP   | 931-254-9 (REACH-IT List-No.)  |
| CAS   | (64742-49-0)   |
| content %   | 10-25  |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225<br>Asp. Tox. 1, H304<br>STOT SE 3, H336<br>Aquatic Chronic 2, H411                        |
| <b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</b>     |  |
| Registration number (REACH)                                 | 01-2119475515-33-XXXX  |
| Index   | ---  |
| EINECS, ELINCS, NLP   | 927-510-4 (REACH-IT List-No.)  |
| CAS   | ---  |
| content %   | 10-<20   |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225<br>Asp. Tox. 1, H304<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Aquatic Chronic 2, H411 |
| <b>Zinc oxide</b>   |  |

Page 3 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

|  |  |
|--|--|
| <b>Registration number (REACH)</b>                                 | --   |
| <b>Index</b>   | 030-013-00-7   |
| <b>EINECS, ELINCS, NLP</b>   | 215-222-5  |
| <b>CAS</b>   | 1314-13-2  |
| <b>content %</b>   | 1-<2,5   |
| <b>Classification according to Regulation (EC) 1272/2008 (CLP)</b> | Aquatic Acute 1, H400 (M=1)<br>Aquatic Chronic 1, H410 (M=1) |

|  |  |
|--|--|
| <b>Amine phosphate</b>   |  |
| <b>Registration number (REACH)</b>                                 | --   |
| <b>Index</b>   | ---  |
| <b>EINECS, ELINCS, NLP</b>   | 279-632-6  |
| <b>CAS</b>   | 80939-62-4   |
| <b>content %</b>   | 0,1-<1   |
| <b>Classification according to Regulation (EC) 1272/2008 (CLP)</b> | Eye Irrit. 2, H319<br>Skin Irrit. 2, H315<br>Aquatic Chronic 2, H411 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

With long-term contact:

drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Gastrointestinal disturbances

Other dangerous properties cannot be ruled out.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO2

Page 4 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 10.07.2015 / 0003  
Replaces revision of / Version: 02.09.2014 / 0002  
Valid from: 10.07.2015  
PDF print date: 15.07.2015  
WD-40® Specialist®Motorbike Chain Wax

Exinction powder  
Water jet spray  
Alcohol resistant foam

### **Unsuitable extinguishing media**

High volume water jet

## **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon  
Oxides of nitrogen  
Oxides of phosphorus  
Toxic gases  
Danger of bursting (explosion) when heated  
Explosive vapour/air mixture

## **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping

### **6.2 Environmental precautions**

Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

If spray or gas escapes, ensure ample fresh air is available.  
Without adequate ventilation, formation of explosive mixtures may be possible.  
Active substance:  
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### **7.1 Precautions for safe handling**

#### **7.1.1 General recommendations**

Ensure good ventilation.  
Avoid inhalation of the vapours.  
Avoid contact with eyes or skin.  
Keep away from sources of ignition - Do not smoke.  
Take measures against electrostatic charging, if appropriate.  
Do not use on hot surfaces.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### **7.1.2 Notes on general hygiene measures at the workplace**

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### **7.2 Conditions for safe storage, including any incompatibilities**

Keep out of access to unauthorised individuals.  
Not to be stored in gangways or stair wells.  
Store product closed and only in original packing.  
Observe special regulations for aerosols!

Page 5 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").  
 Store in a well ventilated place.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store cool

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

| Chemical Name                  | Hydrocarbons, C6, isoalkanes, < 5% n-hexane  | Content %:10-25 |
|--------------------------------|--|-----------------|
| WEL-TWA: 800 mg/m <sup>3</sup> | WEL-STEL: ---  | ---             |
| Monitoring procedures:         | - Draeger - Hydrocarbons 2/a (81 03 581)<br>- Draeger - Hydrocarbons 0,1%/c (81 03 571)<br>- Compur - KITA-187 S (551 174) |                 |
| BMGV: ---                      | Other information: (WEL acc. to RCP-method, EH40)  |                 |

| Chemical Name                         | Hydrocarbons, C6, isoalkanes, < 5% n-hexane  | Content %:10-25 |
|---------------------------------------|--|-----------------|
| OELV-8h: 1200 mg/m <sup>3</sup> (AGW) | OELV-15min: 2(II) (AGW)  | ---             |
| Monitoring procedures:                | - Draeger - Hydrocarbons 2/a (81 03 581)<br>- Draeger - Hydrocarbons 0,1%/c (81 03 571)<br>- Compur - KITA-187 S (551 174) |                 |
| BLV: ---                              | Other information: ---   |                 |

| Chemical Name                  | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics   | Content %:10-<20 |
|--------------------------------|--|------------------|
| WEL-TWA: 800 mg/m <sup>3</sup> | WEL-STEL: ---  | ---              |
| Monitoring procedures:         | - Draeger - Hydrocarbons 2/a (81 03 581)<br>- Draeger - Hydrocarbons 0,1%/c (81 03 571)<br>- Compur - KITA-187 S (551 174) |                  |
| BMGV: ---                      | Other information: (WEL acc. to RCP-method, EH40)  |                  |

| Chemical Name                         | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics   | Content %:10-<20 |
|---------------------------------------|--|------------------|
| OELV-8h: 1200 mg/m <sup>3</sup> (AGW) | OELV-15min: 2(II) (AGW)  | ---              |
| Monitoring procedures:                | - Draeger - Hydrocarbons 2/a (81 03 581)<br>- Draeger - Hydrocarbons 0,1%/c (81 03 571)<br>- Compur - KITA-187 S (551 174) |                  |
| BLV: ---                              | Other information: ---   |                  |

| Chemical Name   | Petroleum gases, liquified   | Content %: |
|---|--|------------|
| WEL-TWA: 1000 ppm (1750 mg/m <sup>3</sup> ) (Liquefied petroleum gas (LPG)) | WEL-STEL: 1250 ppm (2180 mg/m <sup>3</sup> ) (Liquefied petroleum gas (LPG)) | ---        |
| Monitoring procedures:  | ---  |            |
| BMGV: ---   | Other information: ---   |            |

| Chemical Name                               | Petroleum gases, liquified                     | Content %: |
|---|--|------------|
| OELV-8h: 1000 ppm (1800 mg/m <sup>3</sup> ) | OELV-15min: 1250 ppm (2250 mg/m <sup>3</sup> ) | ---        |
| Monitoring procedures:                      | ---  |            |
| BLV: ---                                    | Other information: ---                         |            |

| Chemical Name                        | Oil mist, mineral  | Content %: |
|--------------------------------------|--|------------|
| WEL-TWA: 5 mg/m <sup>3</sup> (ACGIH) | WEL-STEL: 10 mg/m <sup>3</sup> (ACGIH)                                     | ---        |
| Monitoring procedures:               | - Draeger - Oil 10/a-P (67 28 371)<br>- Draeger - Oil Mist 1/a (67 33 031) |            |
| BMGV: ---                            | Other information: ---   |            |

| Chemical Name   | Oil mist, mineral                  | Content %: |
|---|------------------------------------|------------|
| OELV-8h: 0,2 mg/m <sup>3</sup> (Mineral oil, used in metal working (inhalable)), 5 mg/m <sup>3</sup> (Mineral oil, pure, highly & severely refined (inhalable)) | OELV-15min: ---                    | ---        |
| Monitoring procedures:  | - Draeger - Oil 10/a-P (67 28 371) |            |

- Draeger - Oil Mist 1/a (67 33 031)

BLV: ---

Other information: ---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

| Zinc oxide          |  |                             |            |       |              |      |
|---------------------|--|-----------------------------|------------|-------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health            | Descriptor | Value | Unit         | Note |
| Workers / employees | Human - inhalation                         | Long term, systemic effects | DNEL       | 5     | mg/m3        |      |
|                     | Environment - freshwater                   |                             | PNEC       | 20,6  | µg/l         |      |
|                     | Environment - marine                       |                             | PNEC       | 6,1   | µg/l         |      |
|                     | Environment - sewage treatment plant       |                             | PNEC       | 52    | µg/l         |      |
|                     | Environment - sediment, freshwater         |                             | PNEC       | 118   | mg/kg        |      |
|                     | Environment - sediment, marine             |                             | PNEC       | 56,5  | mg/kg        |      |
|                     | Environment - soil                         |                             | PNEC       | 35,6  | mg/kg        |      |
| Workers / employees | Human - oral                               | Short term, local effects   | DNEL       | 62,2  | mg/kg bw/day |      |
| Workers / employees | Human - inhalation                         | Short term, local effects   | DNEL       | 6,2   | mg/m3        |      |
| Consumer            | Human - inhalation                         | Short term, local effects   | DNEL       | 3,1   | mg/m3        |      |
| Workers / employees | Human - dermal                             | Short term, local effects   | DNEL       | 6223  | mg/kg bw/day |      |
| Workers / employees | Human - dermal                             | Long term, local effects    | DNEL       | 83    | mg/kg bw/day |      |
| Workers / employees | Human - inhalation                         | Long term, local effects    | DNEL       | 1,2   | mg/m3        |      |
| Consumer            | Human - inhalation                         | Long term, local effects    | DNEL       | 1,5   | mg/m3        |      |
| Consumer            | Human - dermal                             | Long term, systemic effects | DNEL       | 83    | mg/kg        |      |
| Consumer            | Human - inhalation                         | Long term, systemic effects | DNEL       | 2,5   | mg/m3        |      |
| Consumer            | Human - oral                               | Long term, systemic effects | DNEL       | 0,83  | mg/kg bw/day |      |

| Hydrocarbons, C6, isoalkanes, < 5% n-hexane |  |                             |            |       |            |      |
|---|--|-----------------------------|------------|-------|------------|------|
| Area of application                         | Exposure route / Environmental compartment | Effect on health            | Descriptor | Value | Unit       | Note |
| Workers / employees                         | Human - dermal                             | Long term, systemic effects | DNEL       | 13964 | mg/kg bw/d |      |
| Workers / employees                         | Human - inhalation                         | Long term, systemic effects | DNEL       | 5306  | mg/m3      |      |
| Consumer                                    | Human - dermal                             | Long term, systemic effects | DNEL       | 1377  | mg/kg bw/d |      |
| Consumer                                    | Human - oral                               | Long term, systemic effects | DNEL       | 1301  | mg/kg bw/d |      |

|          |                    |                             |      |      |       |  |
|----------|--------------------|-----------------------------|------|------|-------|--|
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 1131 | mg/m3 |  |
|----------|--------------------|-----------------------------|------|------|-------|--|

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics |  |                             |            |       |              |      |
|--|--|-----------------------------|------------|-------|--------------|------|
| Area of application                              | Exposure route / Environmental compartment | Effect on health            | Descriptor | Value | Unit         | Note |
| Workers / employees                              | Human - dermal                             | Long term, systemic effects | DNEL       | 300   | mg/kg bw/day |      |
| Workers / employees                              | Human - inhalation                         | Long term, systemic effects | DNEL       | 2085  | mg/m3        |      |
| Consumer   | Human - oral                               | Long term, systemic effects | DNEL       | 149   | mg/kg bw/day |      |
| Consumer   | Human - dermal                             | Long term, systemic effects | DNEL       | 149   | mg/kg bw/day |      |
| Consumer   | Human - inhalation                         | Long term, systemic effects | DNEL       | 447   | mg/m3        |      |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Normally not necessary.

In case of direct contact with the ingredients:

If applicable

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

> 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective gloves made of polyvinyl alcohol (EN 374)

Protective Viton® / fluoroelastomer gloves (EN 374)

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |   |
|--|---|
| Physical state:                          | Aerosol, Substance: Liquid  |
| Colour:                                  | White   |
| Odour:                                   | Characteristic  |
| Odour threshold:                         | Not determined  |
| pH-value:                                | Not determined  |
| Melting point/freezing point:            | Not determined  |
| Initial boiling point and boiling range: | Not determined  |
| Flash point:                             | n.a., Aerosol   |
| Evaporation rate:                        | Not determined  |
| Flammability (solid, gas):               | Not determined  |
| Lower explosive limit:                   | Not determined  |
| Upper explosive limit:                   | Not determined  |
| Vapour pressure:                         | Not determined  |
| Vapour density (air = 1):                | Not determined  |
| Density:                                 | Not determined  |
| Bulk density:                            | Not determined  |
| Solubility(ies):                         | Not determined  |
| Water solubility:                        | Insoluble   |
| Partition coefficient (n-octanol/water): | Not determined  |
| Auto-ignition temperature:               | Not determined  |
| Decomposition temperature:               | Not determined  |
| Viscosity:                               | Not determined  |
| Explosive properties:                    | Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture. |
| Oxidising properties:                    | No  |

### 9.2 Other information

|                           |                |
|---------------------------|----------------|
| Miscibility:              | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity:             | Not determined |
| Surface tension:          | Not determined |
| Solvents content:         | Not determined |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not to be expected

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 10.07.2015 / 0003

Replaces revision of / Version: 02.09.2014 / 0002

Valid from: 10.07.2015

PDF print date: 15.07.2015

WD-40® Specialist®Motorbike Chain Wax

Possibly more information on health effects, see Section 2.1 (classification).

**WD-40® Specialist®Motorbike Chain Wax**

| Toxicity / effect   | Endpoint | Value | Unit | Organism | Test method | Notes  |
|---|----------|-------|------|----------|-------------|--|
| Acute toxicity, by oral route:                                |          |       |      |          |             | n.d.a.   |
| Acute toxicity, by dermal route:                              |          |       |      |          |             | n.d.a.   |
| Acute toxicity, by inhalation:                                |          |       |      |          |             | n.d.a.   |
| Skin corrosion/irritation:                                    |          |       |      |          |             | n.d.a.   |
| Serious eye damage/irritation:                                |          |       |      |          |             | n.d.a.   |
| Respiratory or skin sensitisation:                            |          |       |      |          |             | n.d.a.   |
| Germ cell mutagenicity:                                       |          |       |      |          |             | n.d.a.   |
| Carcinogenicity:  |          |       |      |          |             | n.d.a.   |
| Reproductive toxicity:  |          |       |      |          |             | n.d.a.   |
| Specific target organ toxicity - single exposure (STOT-SE):   |          |       |      |          |             | n.d.a.   |
| Specific target organ toxicity - repeated exposure (STOT-RE): |          |       |      |          |             | n.d.a.   |
| Aspiration hazard:  |          |       |      |          |             | n.d.a.   |
| Symptoms:   |          |       |      |          |             | n.d.a.   |
| Other information:  |          |       |      |          |             | Classification according to calculation procedure. |

**Hydrocarbons, C6, isoalkanes, < 5% n-hexane**

| Toxicity / effect                | Endpoint | Value  | Unit    | Organism | Test method                          | Notes  |
|----------------------------------|----------|--------|---------|----------|--------------------------------------|--|
| Acute toxicity, by oral route:   | LD50     | >16750 | mg/kg   | Rat      | OECD 401 (Acute Oral Toxicity)       |  |
| Acute toxicity, by dermal route: | LD50     | >3350  | mg/kg   | Rabbit   | OECD 402 (Acute Dermal Toxicity)     |  |
| Acute toxicity, by inhalation:   | LC50     | 259    | mg/l/4h | Rat      | OECD 403 (Acute Inhalation Toxicity) | Vapours  |
| Aspiration hazard:               |          |        |         |          |                                      | Yes  |
| Symptoms:                        |          |        |         |          |                                      | drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting. |

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics**

| Toxicity / effect                  | Endpoint | Value  | Unit    | Organism | Test method                                  | Notes           |
|------------------------------------|----------|--------|---------|----------|--|-----------------|
| Acute toxicity, by oral route:     | LD50     | >2000  | mg/kg   | Rat      |  |                 |
| Acute toxicity, by oral route:     | LD50     | >8     | ml/kg   | Rat      | OECD 401 (Acute Oral Toxicity)               |                 |
| Acute toxicity, by dermal route:   | LD50     | >=4    | ml/kg   | Rat      | OECD 402 (Acute Dermal Toxicity)             |                 |
| Acute toxicity, by dermal route:   | LD50     | >2000  | mg/kg   | Rat      |  |                 |
| Acute toxicity, by inhalation:     | LC50     | >23,3  | mg/l/4h | Rat      | OECD 403 (Acute Inhalation Toxicity)         |                 |
| Acute toxicity, by inhalation:     | LC50     | >23300 | mg/m3   | Rat      | OECD 403 (Acute Inhalation Toxicity)         |                 |
| Skin corrosion/irritation:         |          |        |         | Rabbit   | OECD 404 (Acute Dermal Irritation/Corrosion) | Irritant        |
| Respiratory or skin sensitisation: |          |        |         |          |  | Not sensitising |
| Germ cell mutagenicity:            |          |        |         |          |  | Negative        |

Page 10 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

|                    |  |  |  |  |  |   |
|--------------------|--|--|--|--|--|---|
| Aspiration hazard: |  |  |  |  |  | Yes   |
| Symptoms:          |  |  |  |  |  | diarrhoea, headaches, dizziness, nausea and vomiting. |

| Zinc oxide                         |          |        |         |          |  |  |
|------------------------------------|----------|--------|---------|----------|--|--|
| Toxicity / effect                  | Endpoint | Value  | Unit    | Organism | Test method                                  | Notes  |
| Acute toxicity, by oral route:     | LD50     | >15000 | mg/kg   | Rat      | OECD 401 (Acute Oral Toxicity)               |  |
| Acute toxicity, by inhalation:     | LC50     | >5,7   | mg/l/4h | Rat      | OECD 403 (Acute Inhalation Toxicity)         |  |
| Skin corrosion/irritation:         |          |        |         | Rabbit   | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant   |
| Serious eye damage/irritation:     |          |        |         | Rabbit   | OECD 405 (Acute Eye Irritation/Corrosion)    | Not irritant   |
| Respiratory or skin sensitisation: |          |        |         |          | OECD 406 (Skin Sensitisation)                | Not sensitising  |
| Germ cell mutagenicity:            |          |        |         |          | (Ames-Test)                                  | Negative   |
| Symptoms:                          |          |        |         |          |  | breathing difficulties, chest pain (thorax pain), diarrhoea, fever, joint pain, coughing, headaches, circulatory disorders, metal fume fever, muscle pains, mucous membrane irritation, nausea and vomiting. |

| Amine phosphate                    |          |        |       |            |  |                 |
|------------------------------------|----------|--------|-------|------------|--|-----------------|
| Toxicity / effect                  | Endpoint | Value  | Unit  | Organism   | Test method                                  | Notes           |
| Acute toxicity, by oral route:     | LD50     | > 2000 | mg/kg | Rat        | OECD 401 (Acute Oral Toxicity)               |                 |
| Acute toxicity, by dermal route:   | LD50     | >2000  | mg/kg | Rat        | OECD 402 (Acute Dermal Toxicity)             |                 |
| Skin corrosion/irritation:         |          |        |       | Rabbit     | OECD 404 (Acute Dermal Irritation/Corrosion) | Irritant        |
| Serious eye damage/irritation:     |          |        |       | Rabbit     | OECD 405 (Acute Eye Irritation/Corrosion)    | Irritant        |
| Respiratory or skin sensitisation: |          |        |       | Guinea pig |  | Not sensitising |

| Petroleum gases, liquified     |          |       |      |          |             |              |
|--------------------------------|----------|-------|------|----------|-------------|--------------|
| Toxicity / effect              | Endpoint | Value | Unit | Organism | Test method | Notes        |
| Acute toxicity, by inhalation: | LC50     | >5    | mg/l |          |             |              |
| Skin corrosion/irritation:     |          |       |      |          |             | Not irritant |
| Serious eye damage/irritation: |          |       |      |          |             | Not irritant |

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| WD-40® Specialist®Motorbike Chain Wax |          |      |       |      |          |             |        |
|---------------------------------------|----------|------|-------|------|----------|-------------|--------|
| Toxicity / effect                     | Endpoint | Time | Value | Unit | Organism | Test method | Notes  |
| Toxicity to fish:                     |          |      |       |      |          |             | n.d.a. |
| Toxicity to daphnia:                  |          |      |       |      |          |             | n.d.a. |
| Toxicity to algae:                    |          |      |       |      |          |             | n.d.a. |
| Persistence and degradability:        |          |      |       |      |          |             | n.d.a. |

|                                    |  |  |  |  |  |  |        |
|------------------------------------|--|--|--|--|--|--|--------|
| Bioaccumulative potential:         |  |  |  |  |  |  | n.d.a. |
| Mobility in soil:                  |  |  |  |  |  |  | n.d.a. |
| Results of PBT and vPvB assessment |  |  |  |  |  |  | n.d.a. |
| Other adverse effects:             |  |  |  |  |  |  | n.d.a. |

**Hydrocarbons, C6, isoalkanes, < 5% n-hexane**

| Toxicity / effect                  | Endpoint | Time | Value   | Unit | Organism            | Test method | Notes  |
|------------------------------------|----------|------|---------|------|---------------------|-------------|--|
| Toxicity to fish:                  | EC50     | 96h  | 18,27   | mg/l | Oncorhynchus mykiss |             |  |
| Toxicity to daphnia:               | EC50     | 48h  | 31,9    | mg/l | Daphnia magna       |             |  |
| Persistence and degradability:     |          | 28d  | 98      | %    |                     |             | Readily biodegradable (Analogous conclusion) |
| Bioaccumulative potential:         | BCF      |      | 242-253 |      |                     |             |  |
| Bioaccumulative potential:         | Log Kow  |      | 2,9-4   |      |                     |             |  |
| Results of PBT and vPvB assessment |          |      |         |      |                     |             | No PBT substance, No vPvB substance          |

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics**

| Toxicity / effect                  | Endpoint | Time | Value | Unit | Organism                         | Test method  | Notes                               |
|------------------------------------|----------|------|-------|------|----------------------------------|--|-------------------------------------|
| Toxicity to fish:                  | LC50     | 96h  | >13,4 | mg/l | Oncorhynchus mykiss              | OECD 203 (Fish, Acute Toxicity Test)                               |                                     |
| Toxicity to daphnia:               | LC50     | 48h  | 3     | mg/l | Daphnia magna                    | OECD 202 (Daphnia sp. Acute Immobilisation Test)                   |                                     |
| Toxicity to daphnia:               | EC50     | 48h  | 3     | mg/l | Daphnia magna                    | OECD 202 (Daphnia sp. Acute Immobilisation Test)                   |                                     |
| Toxicity to daphnia:               | EL50     | 24h  | 12    | mg/l | Daphnia magna                    | OECD 202 (Daphnia sp. Acute Immobilisation Test)                   |                                     |
| Toxicity to daphnia:               | NOELR    | 21d  | 1     | mg/l | Daphnia magna                    | OECD 211 (Daphnia magna Reproduction Test)                         |                                     |
| Toxicity to algae:                 | EL50     | 72h  | 12    | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| Toxicity to algae:                 | NOELR    | 72h  | 6,3   | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| Toxicity to algae:                 | ErL50    | 72h  | 10-30 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| Toxicity to algae:                 | EbL50    | 72h  | 10-30 | mg/l | Pseudokirchnerie lla subcapitata | OECD 201 (Alga, Growth Inhibition Test)                            |                                     |
| Persistence and degradability:     |          | 28d  | 98    | %    |                                  | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) |                                     |
| Results of PBT and vPvB assessment |          |      |       |      |                                  |  | No PBT substance, No vPvB substance |

**Zinc oxide**

| Toxicity / effect              | Endpoint   | Time | Value   | Unit | Organism                         | Test method | Notes                               |
|--------------------------------|------------|------|---------|------|----------------------------------|-------------|-------------------------------------|
| Toxicity to fish:              | LC50       | 96h  | >320    | mg/l | Lepomis macrochirus              |             |                                     |
| Toxicity to fish:              | LC50       | 96h  | 1,1-2,5 | ppm  | Oncorhynchus mykiss              |             |                                     |
| Toxicity to daphnia:           | EC50       | 48h  | 1       | mg/l | Daphnia magna                    |             |                                     |
| Toxicity to algae:             | EC50       | 72h  | 0,136   | mg/l | Selenastrum capricornutum        |             |                                     |
| Toxicity to algae:             | EC50       | 72h  | 0,17    | mg/l | Selenastrum capricornutum        |             |                                     |
| Toxicity to algae:             | NOEC/NO EL | 72h  | 0,017   | mg/l | Pseudokirchnerie lla subcapitata |             |                                     |
| Persistence and degradability: |            |      |         |      |                                  |             | Readily biodegradable               |
| Persistence and degradability: |            |      |         |      |                                  |             | No PBT substance, No vPvB substance |
| Mobility in soil:              |            |      | 158,5   | L/kg |                                  |             |                                     |

| Amine phosphate                |          |      |       |      |                           |  |                                    |
|--------------------------------|----------|------|-------|------|---------------------------|--|------------------------------------|
| Toxicity / effect              | Endpoint | Time | Value | Unit | Organism                  | Test method  | Notes                              |
| Toxicity to fish:              | LC50     | 96h  | 5,5   | mg/l | Brachydanio rerio         | OECD 203 (Fish, Acute Toxicity Test)   |                                    |
| Toxicity to daphnia:           | EC50     | 48h  | 1,2   | mg/l | Daphnia magna             | OECD 202 (Daphnia sp. Acute Immobilisation Test)   |                                    |
| Toxicity to algae:             | EC50     | 72h  | >10   | mg/l | Selenastrum capricornutum | OECD 201 (Alga, Growth Inhibition Test)  |                                    |
| Persistence and degradability: |          |      |       |      |                           |  | Not readily biodegradable          |
| Persistence and degradability: |          |      |       |      |                           |  | Mechanical precipitation possible. |
| Persistence and degradability: |          |      |       |      |                           | OECD 301 B (Ready Biodegradability - Co2 Evolution Test)                                 | Not readily biodegradable          |
| Toxicity to bacteria:          | EC50     | 3h   | > 100 | mg/l | activated sludge          | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) |                                    |

| Petroleum gases, liquified |          |      |       |      |          |             |       |
|----------------------------|----------|------|-------|------|----------|-------------|-------|
| Toxicity / effect          | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| Bioaccumulative potential: |          |      |       |      |          |             | No    |

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Page 13 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

Take full aerosol cans to problem waste collection.  
 Take emptied aerosol cans to valuable material collection.

### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

## SECTION 14: Transport information

### General statements

UN number: 1950

### Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1950 AEROSOLS

Transport hazard class(es): 2.1

Packing group:

Classification code: 5F

LQ (ADR 2015): 1 L

Environmental hazards: environmentally hazardous

Tunnel restriction code: D



### Transport by sea (IMDG-code)

UN proper shipping name:

AEROSOLS (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT,ZINC OXIDE)

Transport hazard class(es): 2.1

Packing group:

EmS: F-D, S-U

Marine Pollutant:

Environmental hazards: environmentally hazardous



### Transport by air (IATA)

UN proper shipping name:

Aerosols, flammable

Transport hazard class(es): 2.1

Packing group:

Environmental hazards: Not applicable



### Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

### Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Directive 2010/75/EU (VOC): 63,6 %

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

F00205

Revised sections:

These details refer to the product as it is delivered.

1 - 16

Page 14 of 16  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revised on / Version: 10.07.2015 / 0003  
 Replaces revision of / Version: 02.09.2014 / 0002  
 Valid from: 10.07.2015  
 PDF print date: 15.07.2015  
 WD-40® Specialist®Motorbike Chain Wax

Employee instruction/training in handling hazardous materials is required.  
 Employee training in handling dangerous goods is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used                             |
|---|--|
| Skin Irrit. 2, H315   | Classification according to calculation procedure. |
| STOT SE 3, H336   | Classification according to calculation procedure. |
| Aquatic Chronic 2, H411   | Classification according to calculation procedure. |
| Aerosol 1, H222   | Classification based on test data.                 |
| Asp. Tox. 1, H304   | Classification according to calculation procedure. |
| Aerosol 1, H229   | Classification based on test data.                 |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Aerosol — Aerosols  
 Asp. Tox. — Aspiration hazard  
 Flam. Liq. — Flammable liquid  
 Aquatic Acute — Hazardous to the aquatic environment - acute  
 Eye Irrit. — Eye irritation

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 DT50 Dwell Time - 50% reduction of start concentration  
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEA European Economic Area  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ERC Environmental Release Categories  
 ES Exposure scenario  
 etc. et cetera  
 EU European Union  
 EWC European Waste Catalogue  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane  
 HGWP Halocarbon Global Warming Potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC Intermediate Bulk Container  
 IBC (Code) International Bulk Chemical (Code)  
 IC Inhibitory concentration  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LC lethal concentration  
 LC50 lethal concentration 50 percent kill  
 LCLo lowest published lethal concentration  
 LD Lethal Dose of a chemical  
 LD50 Lethal Dose, 50% kill  
 LDLo Lethal Dose Low  
 LOAEL Lowest Observed Adverse Effect Level  
 LOEC Lowest Observed Effect Concentration  
 LOEL Lowest Observed Effect Level  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute of Occupational Safety and Health (United States of America)  
 NOAEC No Observed Adverse Effective Concentration  
 NOAEL No Observed Adverse Effect Level  
 NOEC No Observed Effect Concentration  
 NOEL No Observed Effect Level  
 ODP Ozone Depletion Potential  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PAH polycyclic aromatic hydrocarbon  
 PBT persistent, bioaccumulative and toxic  
 PC Chemical product category  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 POCP Photochemical ozone creation potential  
 ppm parts per million  
 PROC Process category  
 PTFE Polytetrafluorethylene  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

Page 16 of 16  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revised on / Version: 10.07.2015 / 0003  
Replaces revision of / Version: 02.09.2014 / 0002  
Valid from: 10.07.2015  
PDF print date: 15.07.2015  
WD-40® Specialist®Motorbike Chain Wax

---

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.